

Device Modeling Report

Components: Solar Cell

Product Name:BP3125

Manufacture:BP Solar

Kawatta-



All rights reserved © 2020 Kawatta-

OverView

This report shows LTspice simulation results of BP3125 characteristics from datasheet.

I-V and P-V characteristics work in STC condition of datasheet.


*STC is Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C

*This model only works at 25°C of LTspice setting and works voltage from 0V – 22.1V

Specification of electrical performance form datasheet (STC)

Parameter	Value
Maximum Power (Pmax)	125W
Maximum Power Voltage (Vmpp)	17.3V
Maximum Power Current (Impp)	7.23A
Open Circuit Voltage (Voc)	22.1V
Short Circuit Current (Isc)	8.02A

Simulation Circuit



*Vcurrent works as Ammeter.


*V1 works as source of dc sweep of BP3125(0V- 23V).

(*This model works from voltage 0V – 22.1V)


*R1 is load resistance (arbitrary value, EX:10Ω).

*“.temp” works as temperature in STC(25°C)

Simulation result



Results of applied to voltage value of datasheet(Electrical performance in STC)



Error between specification and Simulation.

Symbol	Specification	Simulation	%Error
Isc	8.020	8.020	0.000%
Voc	22.100	22.119	0.086%
Vmpp	17.300	17.382	0.474%
Impp	7.230	7.204	-0.364%
Pmax(Impp*Vmpp)	125.079	125.215	0.109%