

# Device Modeling Report

Components: Solar Cell

Product Name:GW-ES230A

Manufacture:GW Solar

Kawatta-



All rights reserved © 2020 Kawatta-

## OverView

This report shows LTspice simulation results of GW-ES230A characteristics from datasheet.

I-V and P-V characteristics work in STC condition of datasheet.


\*STC is Irradiance 1000W/m<sup>2</sup>, AM1.5 spectrum, module temperature 25°C

\*This model only works at 25°C of LTspice setting and works voltage from 0V – 33.95V

## Specification of electrical performance form datasheet (STC)

Parameter	Value
Maximum Power (Pmax)	230W
Maximum Power Voltage (Vmpp)	27.55V
Maximum Power Current (Impp)	8.35A
Open Circuit Voltage (Voc)	33.95V
Short Circuit Current (Isc)	8.69A

## Simulation Circuit



\*Vcurrent works as Ammeter.


\*V1 works as source of dc sweep of GW-ES230A(0V- 34V).

(\*This model works from voltage 0V – 33.95V)


\*R1 is load resistance (arbitrary value, EX:10Ω).

\*“.temp” works as temperature in STC(25°C)

## Simulation result



## Results of applied to voltage value of datasheet(Electrical performance in STC)



## Error between specification and Simulation.

Symbol	Specification	Simulation	%Error
Isc	8.690	8.690	0.000%
Voc	33.950	33.975	0.074%
Vmpp	27.550	27.628	0.283%
Impp	8.350	8.335	-0.181%
Pmax(Impp*Vmpp)	230.043	230.275	0.101%